

FLUID REQUIREMENTS FOR ROTARY LIFT LIGHT DUTY LIFTS

USE DEXRON III ATF OR HYDRAULIC FLUID THAT MEETS ISO 32 SPECIFICATIONS

LIFT MODEL	SYSTEM CAPACITY QUARTS	SYSTEM CAPACITY LITERS
A7i/SPOA7	19 QUARTS	17.98 LITERS
A9i/SPOA9	19 QUARTS	17.98 LITERS
S9i/SPO9	19 QUARTS	17.98 LITERS
S12i/SPO12	19 QUARTS	17.98 LITERS
S15i,S18i/SPO15,18	19 QUARTS	17.98 LITERS
SPOA82	19 QUARTS	17.98 LITERS
TLO7	19 QUARTS	17.98 LITERS
SM7/SM7XLT	6.5 QUARTS	6.15 LITERS
ARO123i	13 QUARTS	12.3 LITERS
SM/AR123	13 QUARTS	12.3 LITERS
SMO/ARO123	13 QUARTS	12.3 LITERS
SM101	13 QUARTS	12.3 LITERS
SM180	13 QUARTS	12.3 LITERS
SM181	13 QUARTS	12.3 LITERS
SM300	22 QUARTS	20.82 LITERS
SM301	22 QUARTS	20.82 LITERS
SM302	22 QUARTS	20.82 LITERS
SL19i	14 QUARTS	13.25 LITERS
SL29i/SL212i	19 QUARTS	17.98 LITERS
VL SERIES	6 QUARTS	5.678 LITERS
VM SERIES	6 QUARTS	5.678 LITERS
PSL6	6 QUARTS	5.678 LITERS