


**ROTARY LIFT**

Optical overhead sensor protects your customers' vehicles from being raised too high. When the light beam is interrupted, the lift stops and alerts the operator.



Overhead non-load bearing cables ensure equalization of carriages.

Power unit is located up and out of the way to reduce noise. This also increases work space yielding easier movement in the bay.

Adjustable height option on two-post column extensions. Gives you flexibility during installation to maximize the vehicles you can service with each lift.




Dual controls allow lift operation from either column. Multi position electronic locking system engages every 3 inches and is fully accessible for maintenance.



OSHA compliant lockable disconnect switch.



Three-position flip-up adapters allow for quick and easy contact with pickup points on a variety of vehicles. We offer the highest standard adapter reach in the industry, often avoiding the need for additional adapters.



Arm restraints make positioning of arms easy. They engage when the lift is raised and automatically disengage when the lift is fully lowered.

Three-position wheel spotting dish helps to provide more accurate spotting of vehicles.



Shown:  
Model A9i  
9,000 lbs. capacity  
shown with optional  
accessories and  
additional equipment.

# Accessories



**MODEL # FJ6137** Required for raising mini-vans with running boards. Adjustable range provides 4 7/8" to 6 3/4" additional height. Rubber contact surface protects undercoated surfaces. Fits any surface mount or inground, frame-engaging, Rotary lift manufactured since October 1973. Includes (4) adapters, mounting rack and hardware.



**MODEL # FJ6139** High step rubber pad adapter provides 2 1/2" additional clearance. Fits any frame engaging Rotary lift manufactured since October 1973. Includes (4) Adapters, mounting rack and hardware.



**MODEL # FJ6138** Rubber pad adapter for protecting new car undercoating, adds 1/2" additional clearance. Fits any frame engaging Rotary lift manufactured since October 1973. Includes (4) adapters, mounting rack and hardware.



**MODEL # FJ6133** Required to lift 1988 or newer General Motors GMT400 pickup trucks. Maximum height 14" depending on lift model. Capacity 2,250 lbs. maximum per adapter. Fits any surface mount or inground, frame-engaging, Rotary lift manufactured since October 1973. Includes (4) adapters, mounting rack and hardware.



**MODEL # FJ6115** Auxiliary adapters for use when raising certain vans or pick-ups. Maximum height 14 3/8" depending on lift model. Capacity 2,250 lbs. maximum per adapter. Fits any surface mount or inground, frame-engaging, Rotary lift manufactured since October 1973. Includes (4) adapters, mounting rack and hardware.



**MODEL # FJ7880** Adapter extension kit for SPOA7-RA, SPOA9-RA & SL29RA models ONLY. Provides additional lifting height when vehicles require additional clearance. For use on front or rear to level vehicle on lift. Includes (4) 3.5" and (4) 5" adapters, mounting rack and hardware.



**MODEL # FA5159** Tool tray kit for models A7i/SPOA7, A9i/SPOA9, S9i/SPO9. Includes two (2) trays, brackets and hardware.



**MODEL # FJ6159** Models SPOA7-RA, SPOA9-RA, SL29RA, A7RA, A9RA and SL29RA ONLY. Adjustable (RA) screw up adapters with rubber pads allow for protection of underbody vehicle components or undercoating.



**MODEL # FJ6100** Includes (4) FJ696, (4) FJ697 and (4) FJ698 plus SP column or wall-mounted adapter organizer rack. Also Available In Different Configurations. Ask Your Distributor For Details.



**MODEL # FA915** (SM/SMO) Air/electric utility box includes filter/ lubricator/regulator. Mounts easily on any column. Provides easy access to both air and electrical outlets making the full rise lift a complete work station.

**MODEL # FA916** (SM/SMO) Same as above excluding filter/ lubricator/regulator.

**MODEL # FA5911** Includes filter / lubricator / regulator. Mounts easily on any Rotary 2-post surface lift (except 84 and 74 series lift). Provides easy access to both air and electrical outlets making the full rise lift a complete work station.

**MODEL # FA5910** As above excluding filter/lubricator/regulator.



**MODEL # PK202SPOA7-225** (Set) Three stage telescoping arms for accommodating smaller vehicles without excessive maneuvering of vehicle. Note: may de-rate lifting capacity. Call factory for details.



**1 FT. 2-POST EXTENDED HEIGHT KIT.**  
MODEL # FJ5107 (A7i/SPOA7);  
MODEL # FJ5109 (A9i/SPOA9);  
MODEL # FJ5111 (S9i/SPO9).

**2 FT. 2-POST EXTENDED HEIGHT KIT.**  
MODEL # FJ5108 (A7i/SPOA7);  
MODEL # FJ5110 (A9i/SPOA9);  
MODEL # FJ5112 (S9i/SPO9).

**4 FT. 2-POST EXTENDED HEIGHT KIT.**  
MODEL # FJ5114 (S9i/SPO9 only).

Kits Include Components necessary to gain Overhead Clearance.



**MODEL # FA5921**  
Magnetic lug-nut tray



**MODEL # FC134-17**  
Portable work step



World